



X500C3

Engine type	10V1600G10F-III A
Alternator type	LSA 47.2 S5
Performance class	G3

GENERAL CHARACTERISTICS

Frequency (Hz)	50
Voltage (V)	400/230
Max power ESP (kVA)	500
Max power ESP (kWe)	400
Max power PRP (kVA)	454.50
Max power PRP (kWe)	363.60
Intensity (A)	722
Standard Control Panel	TELYS
Optional control panel	KERYS

DESCRIPTIVE

- Electronic governor
- Mechanically welded chassis with antivibration suspension
- Main line circuit breaker
- Radiator for wiring temperature of 48/50°C max with mechanical fan
- Protective grille for fan and rotating parts
- 9 dB(A) silencer supplied separately
- Charger DC starting battery with electrolyte
- 24 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation

POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed

TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPA (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

ASSOCIATED UNCERTAINTY

For the generating sets used indoor, where the acoustic pressure levels depends on the installation conditions, it is not possible to specify the ambient noise level in the exploitation and maintenance instructions . You will also find in our exploitation and maintenance instructions a warning concerning the air noise dangers and the need to implement appropriated preventive measures.

DIMENSIONS AND NOISE LEVELS

DIMENSIONS COMPACT VERSION

Length (mm)	3470
Width (mm)	1630
Height (mm)	2075
Dry weight (kg)	4080
Tank capacity (L)	610

DIMENSIONS SOUNDPROOFED VERSION

Canopy	M230
Length (mm).	5031
Width (mm).	1690
Height (mm).	2662
Dry weight (kg).	5670
Tank capacity (L).	610
Acoustic pressure level @1m in dB(A)(N/A)	88
Sound power level guaranteed (Lwa)	108

GENERAL CHARACTERISTICS

Voltage	ESP		PRP		Standby Amps
	kWe	kVA	kWe	kVA	
200/115	400	500	364	455	1443
240 TRI	400	500	364	455	1203
230 TRI	400	500	364	455	1255
220 TRI	400	500	364	455	1312
415/240	400	500	364	455	696
400/230	400	500	364	455	722
380/220	400	500	364	455	760



X500C3

ENGINE SPECIFICATIONS

GENERAL ENGINE DATAS

Engine model	MTU 10V1600G10F-IIIA , 4-temps, Turbo , Air/Air DC 10 X
Cylinder arrangement	V
Displacement (C.I.)	17.53
Bore (mm) x Stroke (mm)	122 x 150
Compression ratio	17.5 : 1
Speed (RPM)	1500
Pistons speed (m/s)	7.50
Maximum stand-by power at rated RPM (kW)	448
Frequency regulation (%)	+/- 0.5%
BMEP (bar)	18.57
Governor type	Electronic

COOLING SYSTEM

Radiator & Engine capacity (L)	100
Max water temperature (°C)	105
Outlet water temperature (°C)	95
Fan power (kW)	14.10
Fan air flow w/o restriction (m3/s)	11.20
Available restriction on air flow (mm EC)	13
Type of coolant	Glycol-Ethylene
Thermostat (°C)	83-95

EMISSIONS

Emission PM (g/kW.h)	<0.2
Emission CO (g/kW.h)	<3.5
Emission HCNOx (g/kWh)	<4
Emission HC (mg/Nm3)	N/A

EXHAUST

Exhaust gas temperature (°C)	500
Exhaust gas flow (L/s)	1560
Max. exhaust back pressure (mm EC)	850

FUEL

Consumption @ 110% load (L/h)	109
Consumption @ 100% load (L/h)	102
Consumption @ 75% load (L/h)	80
Consumption @ 50% load (L/h)	55
Maximum fuel pump flow (L/h)	342

OIL

Oil capacity (L)	60.50
Min. oil pressure (bar)	4
Max. oil pressure (bar)	5
Oil consumption 100% load (L/h)	0.20
Carter oil capacity (L)	53

HEAT BALANCE

Heat rejection to exhaust (kW)	335.92
Radiated heat to ambient (kW)	24
Heat rejection to coolant (kW)	218+99

AIR INTAKE

Max. intake restriction (mm EC)	250
Intake air flow (L/s)	570



X500C3

ALTERNATOR SPECIFICATIONS

GENERAL DATAS

Alternator brand	N/A
Alternator type	LSA 47.2 S5
Number of phase	3
Power factor (Cos Phi)	N/A
Altitude (m)	0 à 1000
Overspeed (rpm)	2250
Number of pole	4
Excitation system	SHUNT
Insulation class / T° class, continuous 40°C	H / H / 125°K
AVR	N/A
Harmonic factor, no load TGH/THC (%)	<1.5
Wave form : NEMA=TIF-(TGH/THC)	<50
Wave form : CEI=FHT-(TGH/THC)	<2
Number of bearing	1
Coupling	Direct
Voltage regulation at established rating (%)	+/- 0.5%
Recovery time (Delta U = 20% transient) (ms)	500 ms

OTHER DATAS

Continuous Nominal Rating 40°C (kVA)	455
Standby Rating 27°C (kVA)	500
Efficiencies 4/4 load (%)	93.80
Air flow (m3/s)	0.90
Short circuit ratio (Kcc)	0.33
Direct axis synchro reactance unsaturated (Xd) (%)	357
Quadra axis synchro reactance unsaturated (Xq) (%)	214
Open circuit time constant (T"do) (ms)	1855
Direct axis transient reactance saturated (X"d) (%)	19.20
Short circuit transient time constant (T"d) (ms)	100
Direct axis subtransient reactance saturated (X""d) (%)	13.50
Subtransient time constant (T""d) (ms)	10
Quadra axis subtransient reactance saturated (X""q) (%)	18
Zero sequence reactance unsaturated (Xo) (%)	0.90
Negative sequence reactance saturated (X2) (%)	15.80
Armature time constant (Ta) (ms)	15
No load excitation current (io) (A)	0.90
Full load excitation current (ic) (A)	3.80
Full load excitation voltage (uc) (V)	38
Recovery time (Delta U = 20% transient) (ms)	500 ms
Engine start (Delta U = 20% perm. or 50% trans.) (kVA)	928
Transient dip (4/4 load) - PF : 0,8 AR (%)	16.70
No load losses (W)	5690
Heat rejection (W)	23780

TELYS, ergonomic and user-friendly

KERYS, coupling and adaptability



The highly versatile TELYS control unit is complex yet accessible, thanks to the particular attention paid to optimising its ergonomics and ease of use. With its large display screen, buttons and scroll wheel, it places the accent on simplicity and communication.

The TELYS offers the following functions:

Electrical measurements: voltmeter, frequency meter, ammeter.

Engine parameters: working hours counter, oil pressure, coolant temperature, fuel level, engine speed, battery voltage.

Alarms and faults: oil pressure, coolant temperature, failure to start, overspeed, alternator min./max., battery voltage min./max., emergency stop, fuel level.

Ergonomics: wheel for navigating around the various menus.

Communication: remote control and operation software, USB connections, PC connection.

For more information on the product and its options, please refer to the sales documentation.

The KERYS control unit has been designed to fulfil the specific requirements of professionals in terms of operating and monitoring generating sets. It therefore offers a wide range of functions. This control unit is fitted as standard to all generating sets designed to be used for coupling and is offered as an option across the rest of our range.

The KERYS can be built into the central console, fitted directly on the generating set, or in a separate cabinet, to fulfil all the requirements for low and high output power plants.

>The KERYS offers the following functions:

Electrical measurements: voltmeter, frequency meter, ammeter.

Engine parameters: working hours counter, oil pressure, coolant temperature, fuel level, engine speed, battery voltage.

Alarms and faults: oil pressure, coolant temperature, failure to start, overspeed, alternator min./max., battery voltage min./max., emergency stop.

Additional functions: coupling, website, diagnostic aid, assistance and maintenance, graphs and archiving, load impact management, 8 available installation configurations, certification in line with international standards.

For more information, please refer to the sales documentation. Additional specifications :Website, Troubleshooting, Assistance and Maintenance, Plotting and logging, Load impact, 8 configurations available, Compliance with international standards...

