

Three Phase String Inverter

SUN-120/125/130/135/136K-G01P3-EU-AM8



8 MPP trackers, Max. efficiency up to 98.8%



Zero export application, VSG application



String intelligent monitoring (optional)



Wide output voltage range



Anti-PID function (Optional)



Type II DC/AC SPD

Deye

Stock Code: 605117.SH

Model	SUN-120K-G01P3 -EU-AM8	SUN-125K-G01P3 -EU-AM8	SUN-130K-G01P3 -EU-AM8	SUN-135K-G01P3 -EU-AM8	SUN-136K-G01P3 -EU-AM8
Input Side					
Max. DC Input Power (kW)	180	187.5	195	202.5	204
Max. DC Input Voltage (V)	1100				
Start-up DC Input Voltage (V)	250				
MPPT Operating Range (V)	200-1000				
Max. DC Input Current (A)	40+40+40+40+40+40+40+40				
Max. Short Circuit Current (A)	60+60+60+60+60+60+60+60				
No.of MPP Trackers	8				
No.of Strings per MPP Tracker	4+4+4+4+4+4+4+4				
Output Side					
Rated Output Power (kW)	120	125	130	135	136
Max. Active Power (kW)	132	135	135	135	136
Nominal Output Voltage / Range (V)	3L/N/PE 220/380V, 230/400V				
Rated Grid Frequency (Hz)	50 / 60 (Optional)				
Operating Phase	Three Phase				
Rated AC Grid Output Current (A)	181.9/174	189.4/181.2	197/188.5	204.6/195.7	206.1/197.2
Max. AC Output Current (A)	200/191.4	204.6/195.7	204.6/195.7	204.6/195.7	206.1/197.2
Output Power Factor	>0.99				
Grid Current THD	<3%				
DC Injection Current (mA)	<0.5%				
Grid Frequency Range	45~55 or 55~65 (Optional)				
Efficiency					
Max. Efficiency	98.8%				
Euro Efficiency	98.3%				
MPPT Efficiency	>99%				
Protection					
DC Reverse-Polarity Protection	Yes				
AC Short Circuit Protection	Yes				
AC Output Overcurrent Protection	Yes				
Output Overvoltage Protection	Yes				
Insulation Resistance Protection	Yes				
Ground Fault Monitoring	Yes				
Anti-islanding Protection	Yes				
Temperature Protection	Yes				
Integrated DC Switch	Yes				
Remote Software Upload	Yes				
Remote Change of Operating Parameters	Yes				
Surge Protection	DC Type II / AC Type II				
General Data					
Cabinet Size (WxHxD mm)	1006×516×325.5 (Excluding Connectors and Brackets)				
Weight (kg)	103				
Topology	Transformerless				
Internal Consumption	<1W (Night)				
Running Temperature	-25-60°C, >45°C Derating				
Ingress Protection	IP65				
Noise Emission (Typical)	≤65 dB				
Cooling Concept	Smart Cooling				
Permissible Altitude (m)	4000				
Designed Lifetime	>20 Years				
Grid Connection Standard	IEC 61727, IEC 62116, EN 50549, VDE-AR-N 4110, NRS 097				
Operating Surroundings Humidity	0-100%				
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2				
Features					
DC Connection	MC-4 Mateable				
AC Connection	IP65 Rated Plug				
Display	LCD 240 × 160				
Interface	RS485/RS232/Wifi/LAN				